



POWER-RADACH.de

Metal flat profile gaskets with layers

revoseal Eco+

The ECO+ gasket consists of a solid stainless steel carrier, with a thin graphite layer on both sides. On the medium side, a resilient cog is embossed, which metallurgically seals on both sides of the flange. The resilient cog can balance forces caused by pressure and temperature fluctuations without being plastically deformed.

Highlights

- › Temperature: -200°C to + 400°C
- › Pressure range : from vacuum to 160 bar (900 lbs)
- › Over-achieves TA-Luft and **VDI 2290** in connection with a leakage check according to **EN 1591-1** (also at using screws of minor quality)
- › Standard material 1.4571 (additional materials on request)
- › Total thickness 1.6 mm (+/- 0.1 mm)
- › Fire Safe Certificate according to **API 607** (also for PTFE) and blow-out resistance according to **VDI 2200**






revoseal Europe GmbH
Industriestr. 1
50259 Pulheim | Germany

T: +49 (0) 2238 47 999-0
F: +49 (0) 2238 47 999-20
info@revoseal.com



Exclusive Distributor for INDIA
JEYSONS INDUSTRIES
L11 to L14, Chaudhary Ind.,
Vakan Pada, Nalasopara East,
Tal. Vasai, Dist. Thane 401209
Mob: +91-9819119925
Email: revoseal@jeysons.com

Type	Cross section	Designation
Eco+		In traditional systems the Eco+ can be used as high-quality replacement for all kinds of flat gaskets up to 2 mm overall height. Due to the thin soft material layers, high surface pressures are already achieved at low bolt forces. At new constructions the Eco+ is the most cost-efficient and technically better alternative to serrated and spiral wound gaskets. Due to the resilient design, retightening of the screws is no longer necessary even at strong pressure and temperature fluctuations.
Eco PU		The Eco PU has a PTFE-U-jacket with diffusion barrier. Therefore, it is best suited for aggressive media in plastic and enamel flanges. Even with low bolt torque forces high surface pressures can be realised.
Eco Top		The Eco TOP has the same properties as the Eco+. It is, however provided with a secondary graphite layer with lower density or PTFE. The secondary seal prevents from flange corrosion as often seen with carbon steel flanges.

Dimensions Eco+

For flanges according DIN2632-2638 – series 1 and DIN EN 1092-1

[DN]	d1					d2					d3						
	PN 10-40	PN 64	PN 100	PN 160	PN 250	PN 10	PN 16	PN 25	PN 40	PN 64	PN 100	PN 160	PN 250	PN 40	PN 64	PN 100	PN 160
15	22	22	22	22	40	40	40	40	40	40	40	51	51	51	61	61	61
20	32	-	-	-	50	50	50	50	50	50	50	61	61	61	-	-	-
25	40	40	40	40	58	58	58	58	58	58	58	71	71	71	82	82	82
32	49	-	-	-	69	69	69	69	69	69	69	82	82	82	-	-	-
40	57	57	57	57	77	77	77	77	77	77	77	92	92	92	103	103	103
50	68	68	68	68	88	88	88	88	88	88	88	107	107	107	113	113	113
65	85	85	85	85	107	107	107	107	107	107	107	127	127	127	138	138	138
80	102	102	102	102	124	124	124	124	124	124	124	142	142	142	148	148	148
100	123	123	123	123	151	151	151	151	151	151	151	162	162	162	174	174	174
125	148	148	148	148	176	176	176	176	176	176	176	192	192	192	210	210	210
150	176	176	176	176	204	204	204	204	204	204	204	218	218	218	224	224	224
200	224	224	224	224	252	252	252	252	252	252	252	268	268	268	290	290	290
250	283	283	283	283	315	315	315	315	315	315	315	328	328	328	352	352	352
300	330	330	330	330	362	362	362	362	362	362	362	378	378	378	400	400	400
350	370	370	370	370	402	402	402	402	402	402	402	412	412	412	424	424	424
400	420	420	420	420	452	452	452	452	452	452	452	468	468	468	486	486	486
450	480	-	-	-	518	518	518	518	518	518	518	539	539	539	-	-	-
500	530	530	530	530	568	568	568	568	568	568	568	594	594	594	628	628	628
600	630	630	630	630	668	668	668	668	668	668	668	695	695	695	731	731	731
700	730	730	730	730	768	768	768	768	768	768	768	810	810	810	852	852	852
800	830	830	830	830	878	878	878	878	878	878	878	917	917	917	942	942	942
900	930	930	930	930	978	978	978	978	978	978	978	1017	1017	1017	1084	1084	1084
1000	1040	1040	1040	1040	1098	1098	1098	1098	1098	1098	1098	1124	1124	1124	1194	1194	1194

DIN / Inch = nominal width • d1 = inside diameter • d2 = outside diameter of the graphite layer • d3 = outside diameter of the gasket

Total thickness is 1.6 +/- 0.1 mm • also available in other DIN and ANSI dimension

Design and calculation according to revoseal factory standard

Dimensions Eco+

For flanges according ANSI B 16.5

[inch]	d1					d2					d3				
	150-400 lbs	600-900 lbs	150 lbs	300 lbs	400 lbs	150 lbs	300 lbs	400 lbs	600 lbs	900 lbs	150 lbs	300 lbs	400 lbs	600 lbs	900 lbs
1/2	18	18	34	34	34	34	34	34	34	34	44,8	50,8	50,8	50,8	60,2
3/4	22	22	40	40	40	40	40	40	40	40	54,2	63,5	63,5	63,5	66,5
1	32	32	50	50	50	50	50	50	50	50	63,5	69,8	69,8	69,8	76,2
1 1/4	40	40	58	58	58	58	58	58	58	58	73,2	79,5	79,5	79,5	85,9
1 1/2	49	49	69	69	69	69	69	69	69	69	82,9	91,9	91,9	91,9	95,6
2	57	57	77	77	77	77	77	77	77	77	101,6	107,9	107,9	107,9	139,7
2 1/2	77	77	97	97	97	97	97	97	97	97	120,6	127,0	127,0	127,0	162,1
3	92	92	114	114	114	114	114	114	114	114	133,3	145,7	145,7	145,7	165,1
3 1/2	115	115	139	139	139	139	139	139	139	139	158,7	161,8	161,8	158,8	-
4	123	123	151	151	151	151	151	151	151	151	171,4	177,8	174,8	190,5	203,1
5	148	148	176	176	176	176	176	176	176	176	193,5	212,6	209,6	238,3	244,3
6	176	176	204	204	204	204	204	204	204	204	218,9	247,3	244,3	263,7	285,7
8	224	224	252	252	252	252	252	252	252	252	276,1	304,8	301,8	317,5	355,6
10	283	283	315	315	315	315	315	315	315	315	336,6	359,0	355,6	396,7	431,8
12	330	330	362	362	362	362	362	362	362	362	406,4	419,1	415,8	453,9	495,3
14	370	370	402	402	402	402	402	402	402	402	447,9	482,6	479,3	489,0	517,7
16	420	420	452	452	452	452	452	452	452	452	511,4	536,4	533,4	562,2	571,5
18	480	480	518	518	518	518	518	518	518	518	546,1	593,6	590,6	609,6	635,0
20	530	530	568	568	568	568	568	568	568	568	603,2	650,7	644,7	679,4	695,5
24	630	630	668	668	668	668	668	668	668	668	714,2	771,7	765,0	787,4	835,2

DIN / Inch = nominal width • d1 = inside diameter • d2 = outside diameter of the graphite layer • d3 = outside diameter of the gasket

Total thickness is 1.6 +/- 0.1 mm • also available in other DIN and ANSI dimension

Design and calculation according to revoseal factory standard